

# Cryoport Express<sup>®</sup> Cryogenic CB1 Shipping System

The **Cryoport Express® CBI Shipping System** is available for various general purpose shipments. Additionally, our Chain of Compliance® ensures that the integrity of sensitive materials is maintained throughout the entire supply chain by providing near-real-time data throughout transit.

Our scientifically engineered liquid nitrogen dry vapor shipping system mitigates risk throughout transportation by leveraging our:

- Smartpak<sup>™</sup> Condition Monitoring System
- · Cryoportal® Logistics Management Platform
- · Live View® Application
- · 24/7/365 Customer Support

Recommended commodities: therapies, vaccines, and other biologic materials.



## Specifications

#### **Temperature Range**

-150°C or colder

#### **Static Hold Time**

Up to 13 days

#### **Dynamic Hold Time**

Up to 10 days

#### Exterior

14.75 L x 14.75 W x 30 H in 37.46 x 37.46 x 76.2 cm

#### Interior Chamber

3.1 in / 7.88 cm diameter 11.5 in / 29.21 cm depth

#### Weight

Dry - 24 lb / 11 kg Charged - 27 lb / 13 kg

#### **Storage Capacity - Canes**

11 canes with sleeves - 55 cryovials - Safepak® 13 canes - 65 cryovials - Cannister

14 canes - 70 cyrovials - Safepak®

15 canes - 75 cryovials

#### **Storage Capacity - Boxes**

2 Cryoport cryovial boxes (5.75 x 2 x 2 in / 146 x 51 x 51 mm) - 30 vials per box (60 total vials)

\*Cryoport cryovial boxes contain vials with 2.0 ml or less

### Benefits

- The Combo Kit Box provides storage for non-temperature sensitive commodities.
- Foam packaging around the dewar neck is constructed to reduce the possibility of impact during shock events.
- Patent-pending retention band ensures the vapor plug remains secured on the dewar regardless of shipping system orientation.
- Foam packaging protects the Smartpak<sup>™</sup> condition monitoring system.
- Includes a designated space for documentation and nontemperature-sensitive accessories.
- Meets ISTA 3A, ISTA 7E, and IATA PI 650.

## Contact Info

cryoport.com info@cryoport.com +1 949.232.1900



<del>-</del>O